

498.00 EUR
incl. 19% VAT, plus shipping



TFT-Display

Front



Rear



Side



Technische Daten

<u>LCD Size</u>	12.1"	<u>Aspect Ratio</u>	4:3
<u>VGA Resolutions</u>	640x480-1024x768	<u>Physikal resolution</u>	800x600
<u>Dot resolution</u>	2400x600	<u>Brightness</u>	400
<u>VGA Input</u>	D-SUB 15	<u>Video Input</u>	2x PAL/NTSC (RCA/S-Video)
<u>Audio Input</u>	--	<u>Touchscreen</u>	USB
<u>Case color</u>	black	<u>Power Input</u>	12VDC
<u>Power Consumption</u>	20W	<u>Case size</u>	310 x 220 x 20mm

Visible area	246 x 184.5 mm	Certificates	CE
Weight	0	Bauform	On-Dash
Warranty months	24		

Features

Adjustable backlight	Auto Power-On
Picture In Picture	IR Remote
Headrest mount	TS pencil
Earphone	Adjustable video aspect
Mirrorable video	Reverse camera input

New from September 2011:

- New panel type (Higher contrast)
- Metal- instead of plastic-enclosure

The CTF-1210 TFT-Display is equipped with a 12.1" TFT panel and comes with many nice features. In any case it is the ideal display- and input-unit for your Laptop, CarPC or HTPC. Because of the 4:3 aspect ratio and the size of 12.1", the display is perfectly suitable for being used in POS-section or on boats. With the touchscreen functionality you easily can control your PC. The brilliant VGA-display ensures a maximum readability and sharpness.

The CTF-1210 can be used with any PC/MAC with VGA- and USB port.

Driver-CD included, compatible with :

- Windows 95/98/ME/NT4/2000/XP
- XP Tablet PC Edition
- Windows CE 2.12, 3.0, .net
- Linux RedHat,Mandrake,..
- Macintosh OS 9.x, 10.x
- DOS,..

Specifications	
<i>Display size</i>	12.1" digital
<i>Aspect ratio</i>	4:3 wide TFT screen
<i>Dot Resolution</i>	2400x600= 1,440,000 dots
<i>Physical Resolution</i>	800x600
<i>Supported Resolutions</i>	640x480-1024x768
<i>Color configuration</i>	RGB stripe
<i>Power input</i>	DC 12VDC
<i>Power consumption</i>	max. 45W
<i>Video system</i>	1x Video input RCA (PAL/NTSC) 1x Video input S-Video 1x VGA input
<i>Dimensions</i>	Display Case : 310mm x 220mm x 20mm Display : 246mm x 184.5mm
<i>Video input signal</i>	1.0Vp-p, composite video
<i>Brightness</i>	400 cd/m ²
<i>Contrast</i>	600:1
<i>Vibration</i>	IEC68-2-6
<i>Operating Temperature</i>	-30° bis 85°C
<i>Features</i>	Full function OSD control (englisch) VESA-mounting holes (75mm)
<i>Scope of supply</i>	- 12.1" VGA Touchscreen TFT with Video-support

	- Mounting unit
	- VGA-connector cable
	- Power supply f. 110/230V Steckdose
	- Cigarette Lighter Adapter
	- USB-connector cable
	- Touchscreen Driver-CD
	- Manual