



98.00 EUR
incl. 19% VAT, plus shipping

- DirectX 10 !
- Mini-PCI Express !



Support:  [Specifications \[EN\]](#)

Specifications

CPU	AMD AM2	RAM	2x SO-DDR-II
Graphic	ATI Radeon HD 4200	Audio	Realtek ALC662 6-Channel HD
Formfactor	ITX (17x17cm)	Base	

Interface

USB	10x USB2.0	LAN	1x 10/100/1000
Firewire	--	Parallel	--
IDE/SATA	4x SATA (RAID)	Serial	1x

Features

TV-Out	■	Passive cooling	
PCI	■	PCI-Express	
Mini-PCI	■	PCMCIA	
IDE		SATA	■
DVI	■	CPU changeable	■
800x480 Resolution	■	Compact Flash	

Compatible enclosures



[CFI A-7879 enclosure \(4x 3.5" NAS, 1x 2.5", Hot-Plug, 1x PCI, 200W \) *new*](#)



[Casetronic Travla C137](#)



[Casetronic Travla C138](#)



[M300 Enclosure \(1x PCI\)](#)



[M300-LCD Enclosure \(1x PCI\)](#)



[M350 Mini-ITX enclosure](#)



[M4-BOX](#)



[MHero-L-B enclosure \(1x PCI, Slimline ODD\)](#)



[MHero-L-R enclosure \(1x PCI, Slimline ODD\) *new*](#)



[MHero-S-B enclosure *new*](#)



[MHero-S-R enclosure *new*](#)



[Morex Case Cubid CB3677 black](#)



[Morex Case Cubid CB3688 black](#)

- AMD RS785 Chipset + SB750 Chipset
- Support Socket AM2+ Quad core Opteron™ & Phenom™
- Support HT3.0 Technology
- Integrated ATI Radeon HD 4200(Support Microsoft DX 10.1)
- Support 4 Serial ATA2 Devices with RAID 0,1,5,10
- Support Dual Channel DDR2 800/667
- Integrated ALC662 HD Audio CODEC with 6-CH
- Support DVI-D/HDMI Output
- Supports 10/100M LAN / Gigabit LAN
- Compliance with EuP standard
- Support CPU Smart FAN
- Ready for Windows® 7™
- 17 x 17CM Mini-ITX Form Factor

Form Factor

Mini-ITX 170 mm x 170 mm

CPU

Support AMD Socket AM2/AM2+

Memory

2 * 240-pin DIMM socket for unbuffered Dual DDR2 800 SDRAM up to 4GB

Chipset

AMD RS785 Chipset + SB750 Chipset
Embedded SB750 Chipset

Serial ATA Interface

4 * Serial ATA2 3Gb/s connectors
Supports HDDs with RAID 0, 1,5,10 functions

Audio Interface

Realtek ALC662 6-Channel HD Audio CODEC

LAN Interface

Realtek RTL8111DL PCI-E LAN chip for 10/100M LAN / Gigabit LAN

Extended Interface

1 * 32-bit PCI Slot
1 * Mini-PCI-E connector

Internal I/O Port	2 * USB 2.0/1.1 headers for 4 USB 2.0 ports CPU / Chassis Fan connectors; 1 * 4-pin ATX 12V Power connector 1 * 20-pin ATX Power connector
BIOS	1 * COM header 8 MB SPI Flash ROM
External I/O Port	6 * USB 2.0/1.1 ports 1 * PS2 KB/MS port 1 * RJ-45 port & 2 * e-SATA ports 1 * Audio I / O ports 1 * VGA port 1 * DVI-D port 1 * HDMI port
Special Features	Advanced Power Design that supports the latest Socket-AM2+ CPU "IMAGE IT!" System Backup Software and "ProMagicPLUS!" System Recovery System
Dimension	170mm x 170mm - Jetway JNC84-E ITX mainboard
Lieferumfang	- DriverCD, Manual - I/O Shield - 2x SATA cable - 1x COM connector cable