



999.00 EUR
incl. 19% VAT, plus shipping

- LVDS

Specifications

CPU	VIA C3 600Mhz	RAM	1x DDR 266
Graphic	VIA UniChrome	Audio	VIA VT1616 6 channel AC97
Formfactor	ITX (17x17cm)	Base	VIA ITX

Interface

USB	4x USB 2.0	LAN	1x 10/100
Firewire	1x	Parallel	1x
IDE/SATA	2x IDE	Serial	1x

Features

TV-Out	■	Passive cooling	■
PCI	■	PCI-Express	
Mini-PCI		PCMCIA	■
IDE	■	SATA	
DVI		CPU changeable	
800x480 Resolution		Compact Flash	■

Compatible enclosures

	Casetronic Travla C137		Casetronic Travla C138 (not in stock until 15.02.2012)
	M200 Enclosure		M200-LCD Enclosure
	M300 Enclosure (1x PCI)		M300-LCD Enclosure (1x PCI) [Delivery time on request]
	M350 Mini-ITX enclosure		Morex Case Cubid CB2699 beige
	Morex Case Cubid CB2699 black		Morex Case Cubid CB3677 black
	Morex Case Cubid CB3688 black		VoomPC (perfect for M1-ATX/M2-ATX) [Black Edition]



[VoomPC \(perfect for
M1-ATX/M2-ATX\) \[Black Edition\]
\(with TFT power connector\)](#)



[VoomPC-2 \(perfect for
M1-/M2-ATX\) \[Black Edition\]](#)



[VoomPC-2 \(perfect for
M1-/M2-ATX\) \[Black Edition\]
\(with TFT power connector\)](#)

VIA EPIA M-II 6000E

- CPU EDEN 600MHz
 - 1x DIMM DDR-266 1xPCI
 - LAN 10/100 / 2xUSB 2.0 / Audio 5.1
 - Graphic integ.CastleRock with MPEG-2
 - 2x FireWire 1xinter 1x extern
 - 1x Floppy Connector / 2xIDE 133/100/66
 - MultiMediaChip / CardBus+CF-Slot
 - TV-Out
- >