



198.00 EUR  
incl. 19% VAT, plus shipping

- Pentium-M/Celeron-M
- Ideal for M2-ATX
- Mini-PCI slots

Support: [Manual \[EN\]](#)

### Specifications

<a href="#">CPU</a>	Intel Pentium-M/Celeron-M @ 400/533 FSB	<a href="#">RAM</a>	1x DDR 266/333
<a href="#">Graphic Formfactor</a>	Intel Extreme Graphics ITX (17x17cm)	<a href="#">Audio Base</a>	Realtek ALC655 5.1 AC97 Intel ITX

### Interface

<a href="#">USB</a>	4x USB 2.0	<a href="#">LAN</a>	1x 10/100
<a href="#">Firewire</a>	--	<a href="#">Parallel</a>	1x
<a href="#">IDE/SATA</a>	2x IDE	<a href="#">Serial</a>	2x

### Features

<a href="#">TV-Out</a>	■	<a href="#">Passive cooling</a>	
<a href="#">PCI</a>	■	<a href="#">PCI-Express</a>	
<a href="#">Mini-PCI</a>	■	<a href="#">PCMCIA</a>	
<a href="#">IDE</a>	■	<a href="#">SATA</a>	
<a href="#">DVI</a>	■	<a href="#">CPU changeable</a>	■
<a href="#">800x480 Resolution</a>	■	<a href="#">Compact Flash</a>	

### Compatible enclosures



[CFI A-7879 enclosure \(4x 3.5" NAS, 1x 2.5", Hot-Plug, 1x PCI, 200W \) \\*new\\*](#)



[Casetronic Travla C137](#)



[Casetronic Travla C138](#)



[M300 Enclosure \(1x PCI\)](#)

	<a href="#">M300-LCD Enclosure (1x PCI)</a>		<a href="#">M350 Mini-ITX enclosure</a>
	<a href="#">M4-BOX</a>		<a href="#">MHero-L-B enclosure (1x PCI, Slimline ODD)</a>
	<a href="#">MHero-L-R enclosure (1x PCI, Slimline ODD) *new*</a>		<a href="#">MHero-S-B enclosure *new*</a>
	<a href="#">MHero-S-R enclosure *new*</a>		<a href="#">Morex Case Cubid CB2699 beige</a>
	<a href="#">Morex Case Cubid CB2699 black</a>		<a href="#">Morex Case Cubid CB3677 black</a>
	<a href="#">Morex Case Cubid CB3688 black</a>		<a href="#">VoomPC (perfect for M1-ATX/M2-ATX) [Black Edition]</a>
	<a href="#">VoomPC (perfect for M1-ATX/M2-ATX) [Black Edition] (with TFT power connector)</a>		<a href="#">VoomPC-2 (perfect for M1-/M2-ATX) [Black Edition]</a>
	<a href="#">VoomPC-2 (perfect for M1-/M2-ATX) [Black Edition] (with TFT power connector)</a>		

- for Pentium-M and Celeron-M CPUs, 533/400FSB up to 2.26 GHz
- 1x 184-pin DIMM socket (DDR 200/266/333, up to 1GB)
- 1x 44-pin Standard-IDE Port
- 1x 40-pin Slim-IDE Port (for 2.5" HDD)
- 1x PCI
- 2x Mini-PCI
- 1x Gigabit LAN
- Graphics adapter onboard (Intel Extreme Technology)
- Sound onboard (Realtek ALC655 5.1 AC97)
- Standard ATX power connector
- TV-Out

**Scope of supply :**

- LV675D mainboard
- Slim CPU Alu cooler
- DVI output cable kit
- IDE-cable (40 pin)
- IDE-cable (44 pin)
- Floppy-cable (26 pin)
- COM-port-cable-kit

Manual online : [Here](#)

Graphics driver for 800x480 resolution : [Here](#)

**Spezifikationen :**

<b>Form Factor</b>	Mini-ITX form factor at 170 x 170 mm
<b>CPU</b>	Micro-FCPGA 478 Mobile Intel Pentium M / Celeron M CPU up to 2.26 GHz @ 400/533 MHz FSB
<b>Memory</b>	One 184-pin DIMM socket Support up to 1 GBytes DDR 200/266/333 SDRAM
<b>Chipset</b>	Intel high performance chipset
<b>Watchdog Timer</b>	Generates a system reset with internal timer for 1 to 255 sec.
<b>Power Management</b>	ACPI 2.0 compliant, supports power saving mode .
<b>Real Time Clock</b>	Intel ICH4 built-in RTC with onboard lithium battery
<b>PCI Enhanced IDE</b>	40-pin UltraATA/100 bus master IDE channels And one onboard 44-pin IDE connector
<b>VGA Interface</b>	Built-in Intel Extreme Graphics Video Memory up to 64 MB shared with system External DB15 female connector on rear I/O panel
<b>LVDS /DVI Interface</b>	Optional Dual channel 18/24-bit LVDS or DVI interface
<b>TV-out Interface</b>	S-video & Composite TV-out
<b>LAN Interface</b>	Intel 82541PI Giga Mbps Ethernet interface
<b>Audio Interface</b>	Onboard ACL655 AC97 3D audio codec 5.1 channel, line-in, line-out, Mic-in, CD-in and S/P DIF interface
<b>Hi-Speed USB 2.0</b>	Intel ICH4 chipset built-in Hi-Speed USB 2.0 interface with 480 Mbps of data transfer rate and bootable setting in BIOS
<b>Multi-I/O Port</b>	1 x RS232 & 1 x RS232/422/485, 1 x parallel, 4 x USB 2.0, 1 x IrDA, 1 x FDD, 8-bit GPIO, 1 x PS/2 keyboard and mouse port.
<b>Solid State Disk</b>	IDE support DiskOn Module with +5V power supply
<b>Expansive Slot</b>	One 32-bit PCI slot supports 2 bus master PCI via riser card, and 2 x Mini-PCI
<b>Environment</b>	Power Requirement: Standard 20/24-pin ATX power supply Dimension (W x L): 170mm x 170mm with standard Mini-ITX form factor Operation Temperature: 0 ~ 60oC (32 ~ 140oF)