



198.00 EUR
incl. 19% VAT, plus shipping

- Pentium-M/Celeron-M
- Ideal for M2-ATX
- Mini-PCI slots

Support: [Manual \[EN\]](#)

Specifications

CPU	Intel Pentium-M/Celeron-M @ 400/533 FSB	RAM	1x DDR 266/333
Graphic Formfactor	Intel Extreme Graphics ITX (17x17cm)	Audio Base	Realtek ALC655 5.1 AC97 Intel ITX

Interface

USB	4x USB 2.0	LAN	1x 10/100
Firewire	--	Parallel	1x
IDE/SATA	2x IDE	Serial	2x

Features

TV-Out	■	Passive cooling	
PCI	■	PCI-Express	
Mini-PCI	■	PCMCIA	
IDE	■	SATA	
DVI	■	CPU changeable	■
800x480 Resolution	■	Compact Flash	

Compatible enclosures



[CFI A-7879 Gehäuse \(4x 3.5" NAS, 1x 2.5", Hot-Plug, 1x PCI, 200W \) *new*](#)


















[Casetronic Travla C137](#)



[Casetronic Travla C138 \(not in stock until 15.02.2012\)](#)



[M300 Enclosure \(1x PCI\)](#)

	M300-LCD Enclosure (1x PCI) [Delivery time on request]		M350 Mini-ITX enclosure
	M4-BOX		MHero-L-B enclosure (1x PCI, Slimline ODD)
	MHero-L-R enclosure (1x PCI, Slimline ODD) *new*		MHero-S-B enclosure *new*
	MHero-S-R enclosure *new*		Morex Case 3777 black
	Morex Case Cubid CB2699 beige		Morex Case Cubid CB2699 black
	Morex Case Cubid CB3677 black		Morex Case Cubid CB3688 black
	VoomPC (perfect for M1-ATX/M2-ATX) [Black Edition]		VoomPC (perfect for M1-ATX/M2-ATX) [Black Edition] (with TFT power connector)
	VoomPC-2 (perfect for M1-/M2-ATX) [Black Edition]		VoomPC-2 (perfect for M1-/M2-ATX) [Black Edition] (with TFT power connector)

- for Pentium-M and Celeron-M CPUs, 533/400FSB up to 2.26 GHz
- 1x 184-pin DIMM socket (DDR 200/266/333, up to 1GB)
- 1x 44-pin Standard-IDE Port
- 1x 40-pin Slim-IDE Port (for 2.5" HDD)
- 1x PCI
- 2x Mini-PCI
- 1x Gigabit LAN
- Graphics adapter onboard (Intel Extreme Technology)
- Sound onboard (Realtek ALC655 5.1 AC97)
- Standard ATX power connector
- TV-Out

Scope of supply :

- LV675D mainboard
- Slim CPU Alu cooler
- DVI output cable kit
- IDE-cable (40 pin)
- IDE-cable (44 pin)
- Floppy-cable (26 pin)
- COM-port-cable-kit

Manual online : [Here](#)

Graphics driver for 800x480 resolution : [Here](#)

Spezifikationen :

Form Factor	Mini-ITX form factor at 170 x 170 mm
CPU	Micro-FCPGA 478 Mobile Intel Pentium M / Celeron M CPU up to 2.26 GHz @ 400/533 MHz FSB
Memory	One 184-pin DIMM socket Support up to 1 GBytes DDR 200/266/333 SDRAM
Chipset	Intel high performance chipset
Watchdog Timer	Generates a system reset with internal timer for 1 to 255 sec.
Power Management	ACPI 2.0 compliant, supports power saving mode .
Real Time Clock	Intel ICH4 built-in RTC with onboard lithium battery
PCI Enhanced IDE	40-pin UltraATA/100 bus master IDE channels And one onboard 44-pin IDE connector
VGA Interface	Built-in Intel Extreme Graphics Video Memory up to 64 MB shared with system External DB15 female connector on rear I/O panel
LVDS /DVI Interface	Optional Dual channel 18/24-bit LVDS or DVI interface
TV-out Interface	S-video & Composite TV-out
LAN Interface	Intel 82541PI Giga Mbps Ethernet interface
Audio Interface	Onboard ACL655 AC97 3D audio codec 5.1 channel, line-in, line-out, Mic-in, CD-in and S/P DIF interface
Hi-Speed USB 2.0	Intel ICH4 chipset built-in Hi-Speed USB 2.0 interface with 480 Mbps of data transfer rate and bootable setting in BIOS
Multi-I/O Port	1 x RS232 & 1 x RS232/422/485, 1 x parallel, 4 x USB 2.0, 1 x IrDA, 1 x FDD, 8-bit GPIO, 1 x PS/2 keyboard and mouse port.
Solid State Disk	IDE support DiskOn Module with +5V power supply
Expansive Slot	One 32-bit PCI slot supports 2 bus master PCI via riser card, and 2 x Mini-PCI
Environment	Power Requirement: Standard 20/24-pin ATX power supply Dimension (W x L): 170mm x 170mm with standard Mini-ITX form factor Operation Temperature: 0 ~ 60oC (32 ~ 140oF)