

999.00 EUR

incl. 19% VAT, plus shipping

- Navilock NL-309T



- Win 98/Me/W2K/MAC/Linux
- Low Power Chipset
- Protokoll: NMEA-0183 v2.0 GGA, GSA, GSV,RMC, VTG, GLL, GNS 2.0

Some optionally available Connection cables :

- IP36 (for IPAQ 36xx/37xx Series)
- IP38 (for IPAQ 22xx/38xx/39xx/54xx Series)
- LOOX (for Siemens Pocket Loox Series)
- P500 (for Palm 500 Series, conditionally for Palm Tungsten)
- PAMV (for Palm V Series)
- PD/Mitac/Yakumo (for Packard Bell-Pocketgear 2030/2060 and for Mitac Mio 528 series, MMIO- and for Yakumo)
- RS232 (for connecting to serial interface)
- SNCN (for Sony Clie N Series)
- SNCT (for Sony Clie T 415 Series)
- T740 (for Toshiba e-740 Serie, 330 & 350)
- USB (for connecting to USB-interface)
- XDA2 (for T mobile MDA XDA2)
- Acer (Pocket Series, N20)
- Asus (for AD 600 Series)
- C125 (for Casio E-125, E-500 Series)
- C200 (for Casio E-200 Series)
- HPJ5 (for HP Jornada 520,525,54x/56x Series)
- Dell Axim (for DELL Pocket Series (Axim))