

999.00 EUR
incl. 19% VAT, plus shipping



- DDR-II !
- FANLESS !
- 1.2 Ghz !
- 6W !

Specifications

CPU	VIA EDEN 1.2Ghz	RAM	1x DDR-II 400/533
Graphic	S3 UniChrome Pro 3D 128bit	Audio	AC97 Codec
Formfactor	ITX (17x17cm)	Base	VIA ITX

Interface

USB	8x USB 2.0	LAN	1x 10/100
Firewire	2x	Parallel	1x
IDE/SATA	2x IDE, 2x SATA	Serial	1x

Features

TV-Out	■	Passive cooling	■
PCI	■	PCI-Express	
Mini-PCI		PCMCIA	
IDE	■	SATA	■
DVI		CPU changeable	
800x480 Resolution		Compact Flash	

Compatible enclosures



[Casetronic Travla C137](#)



[Casetronic Travla C138](#)



[M200 Enclosure](#)



[M200-LCD Enclosure](#)



[M300 Enclosure \(1x PCI\)](#)



[M300-LCD Enclosure \(1x PCI\)](#)



[M350 Mini-ITX enclosure](#)



[Morex Case Cubid CB2699 beige](#)



[Morex Case Cubid CB2699 black](#)



[Morex Case Cubid CB3677 black](#)



[Morex Case Cubid CB3688 black](#)



[VoomPC \(perfect for M1-ATX/M2-ATX\) \[Black Edition\]](#)



[VoomPC \(perfect for M1-ATX/M2-ATX\) \[Black Edition\] \(with TFT power connector\)](#)



[VoomPC-2 \(perfect for M1-/M2-ATX\) \[Black Edition\]](#)



[VoomPC-2 \(perfect for M1-/M2-ATX\) \[Black Edition\] \(with TFT power connector\)](#)

This board is based on the latest VIA C7 architecture.

Processor	VIA C7 1.2 GHz processor
Chipset	VIA CN700 north bridge
	VIA VT8237R south bridge
System Memory	1 DDR2 400/533 DIMM
	Up to 1GB memory size
VGA	Integrated VIA UniChrome AGP graphics
Expansion Slots	1 PCI
Onboard IDE	4 Ultra DMA 133
Onboard Serial ATA	2 SATA connectors
Onboard Floppy	1 Floppy Port
Onboard USB	8 USB 2.0
Onboard LAN	VIA 6103 10/100
Onboard Audio	ALC655 6 channel AC'97 codec
Onboard TV Out	VIA VT1622A TV encoder
Onboard 1394	IEEE 1394
Back Panel I/O	1 1394
	1 RCA video
	1 VGA port
	2 USB 2.0
	1 LAN port
	2 IEEE 1394 ports
	1 serial ports
	1 PS2 mouse port
	1 PS2 keyboard port
	3 audio jacks: line-out, line-in, and mic-in

Onboard I/O Connectors	3 USB 2.0 connectors for 6 USB ports 1 parallel port 1 VGA port 2 serial ports 1 PS2 keyboard connector 1 PS2 mouse connector 1 floppy port Line-in/out/MIC audio ports
BIOS	Award BIOS LPC 4Mbit Flash memory
System Monitoring & Management	CPU temperature Modem ring wake up RTC Alarm Keyboard power on System temperature System voltage Fan speed
Operating Humidity	0% - 95% (relative humidity; non-condensing)
Form Factor	Mini-ITX (17cm x 17cm) ATA 133 flat cable (40 wire, 80 conductor, 3 connectors)
Includes	CD SATA Cable Floppy Cable