



999.00 EUR
incl. 19% VAT, plus shipping

- LVDS edition

Specifications

CPU	VIA C3 1.0Ghz	RAM	1x DDR 266
Graphic	VIA UniChrome	Audio	VIA VT1616 6 channel AC97
Formfactor	ITX (17x17cm)	Base	VIA ITX

Interface

USB	4x USB 2.0	LAN	1x 10/100
Firewire	2x	Parallel	1x
IDE/SATA	2x IDE	Serial	1x

Features

TV-Out	■	Passive cooling
PCI	■	PCI-Express
Mini-PCI		PCMCIA
IDE	■	SATA
DVI		CPU changeable
800x480 Resolution		Compact Flash

Compatible enclosures



[Casetronic Travla C134](#)



[Casetronic Travla C137](#)



[Casetronic Travla C138 \(not in stock until 15.02.2012\)](#)



[M200 Enclosure](#)



[M200-LCD Enclosure](#)










[M300 Enclosure \(1x PCI\)](#)



[M300-LCD Enclosure \(1x PCI\)](#)
[\[Delivery time on request\]](#)



[M350 Mini-ITX enclosure](#)

	M4-BOX		MHero-L-B enclosure (1x PCI, Slimline ODD)
	MHero-L-R enclosure (1x PCI, Slimline ODD) *new*		MHero-S-B enclosure *new*
	MHero-S-R enclosure *new*		Morex Case 3300
	Morex Case 3310		Morex Case 3777 black
	Morex Case Cubid CB2699 beige		Morex Case Cubid CB2699 black
	Morex Case Cubid CB3677 black		Morex Case Cubid CB3688 black
	VoomPC (perfect for M1-ATX/M2-ATX) [Black Edition]		VoomPC (perfect for M1-ATX/M2-ATX) [Black Edition] (with TFT power connector)
	VoomPC-2 (perfect for M1-/M2-ATX) [Black Edition]		VoomPC-2 (perfect for M1-/M2-ATX) [Black Edition] (with TFT power connector)

At just 17cm x 17cm, Mini-ITX is the world's smallest native x86 mainboard platform, and is fully compatible with Microsoft® and Linux Operating Systems.

Now what is this board offering you ?

- 1x DDR266 memory-slot (up to 1024 MB)
- integrated AGP-graphics adapter with MPEG2-decoder (for DVD) (1x VGA-Output , 1x TV-Out(S-Video))
- 1x PCI-Slot (extendable with Riser-Card)
- 2x UltraDMA-133 for drives,1x Floppy-connector
- CPU VIA C3 "Nehemiah" 1,0 GHz with fan
- Connectors : 1xSerial,1xParallel,2xPS/2 (Tastatur,Mouse)
- 4x USB 2.0 connectors
- 2x Firewire
- Sound 1x LineIn,1x Microphon, 1x LineOut and 1x digital(koaxial)
- LAN-Interface 1x RJ-45 (10/100 Mbit)
- LVDS connector onboard

The VIA C3 processor with 1000 MHz has a fan and is already mounted hard on the board and therefor not changeable

The 40-mm-fan makes noises at about 2,9 Sone / 38,9 dBA.

The onboard AGP-graphics-adapter uses between 8 and 64 MB of the main-meory as graphic memory.

For proper DVD-Playback, a MPEG2-decoder-chip is installed.

The S/PDIF-Output can be switched into Cinch-TV-Output-mode. The third and fourth USB-ports, both FireWire-ports, and the second serial port are available only with an optional adaptercable.

More informations on the website of the manufacturer : [VIA](#)