



999.00 EUR  
incl. 19% VAT, plus shipping

### Specifications

<a href="#">CPU</a>	VIA C7 1.5Ghz	<a href="#">RAM</a>	1x DDR-II 400/533
<a href="#">Graphic</a>	VIA UniChrome PRO	<a href="#">Audio</a>	VIA VT1618 6 channel AC97 Codec
<a href="#">Formfactor</a>	ITX (17x17cm)	<a href="#">Base</a>	VIA ITX

### Interface

<a href="#">USB</a>	6x USB 2.0	<a href="#">LAN</a>	1x 10/100/1000 Mbit
<a href="#">Firewire</a>	1x	<a href="#">Parallel</a>	1x
<a href="#">IDE/SATA</a>	2x IDE, 2x SATA	<a href="#">Serial</a>	2x

### Features

<a href="#">TV-Out</a>	■	<a href="#">Passive cooling</a>	
<a href="#">PCI</a>	■	<a href="#">PCI-Express</a>	
<a href="#">Mini-PCI</a>		<a href="#">PCMCIA</a>	
<a href="#">IDE</a>	■	<a href="#">SATA</a>	■
<a href="#">DVI</a>		<a href="#">CPU changeable</a>	
<a href="#">800x480 Resolution</a>		<a href="#">Compact Flash</a>	

### Compatible enclosures



[Casetronic Travla C137](#)



[Casetronic Travla C138](#)



[M200 Enclosure](#)



[M200-LCD Enclosure](#)



[M300 Enclosure \(1x PCI\)](#)



[M300-LCD Enclosure \(1x PCI\)](#)



[M350 Mini-ITX enclosure](#)



[M4-BOX](#)



[MHero-L-B enclosure \(1x PCI,  
Slimline ODD\)](#)



[MHero-L-R enclosure \(1x PCI,  
Slimline ODD\) \\*new\\*](#)



[MHero-S-B enclosure \\*new\\*](#)

[Morex Case Cubid CB2699 beige](#)

[Morex Case Cubid CB3677 black](#)

[VoomPC \(perfect for M1-ATX/M2-ATX\) \[Black Edition\]](#)

[VoomPC-2 \(perfect for M1-/M2-ATX\) \[Black Edition\]](#)



[MHero-S-R enclosure \\*new\\*](#)

[Morex Case Cubid CB2699 black](#)

[Morex Case Cubid CB3688 black](#)

[VoomPC \(perfect for M1-ATX/M2-ATX\) \[Black Edition\] \(with TFT power connector\)](#)

[VoomPC-2 \(perfect for M1-/M2-ATX\) \[Black Edition\] \(with TFT power connector\)](#)

- CPU: VIA C7 1500MHz CN700FSB400
- Processor is cooled actively
- 1x DDR II 533MHz max 1GB / 1x PCI
- 1x 10/100/1000 LAN
- 2x ATA 133/100/66
- 6x USB 2.0 / 1xFireWire
- Sound & Graphics (UniChrome) on Board
- TV-Out
- incl. LVDS-connector

The VIA EPIA EN Mini-ITX mainboard is the first to feature the VIA C7 and VIA Eden processor with the new VIA V4 bus. Combining extra performance with the signature quiet, cool operation and comprehensive feature set integrated into a small form factor, the VIA EPIA EN Mini-ITX mainboard the solution of choice for next generation digital home, business and embedded devices.

Based on the proven CoolStream™ architecture and the advanced 90nm SOI process, the VIA C7 processor delivers leading performance per watt, and utilizes the new 400MHz V4 bus. Fully compatible with Microsoft® Windows® and Linux operating systems, the VIA EPIA EN Mini-ITX mainboard also offers advanced hardware security features through the VIA PadLock Security Engine integrated into the VIA C7 processor, boasting a comprehensive set of military-grade cryptography tools.

The new VIA CN700 digital media IGP chipset features unprecedented CPU bandwidth, full DDR2 memory support, and integrated VIA UniChrome™ Pro 2D/3D graphics with MPEG-2 decoding for smooth digital video playback, while the HDTV encoder provides display flexibility. Also supported is a series of advanced storage and connectivity options, including full LVDS support for seamless integration into LCD panels, S-Video and RCA output, IEEE 1394, USB 2.0 connections and a Gigabit LAN connection for high-speed transmission of data. 24/7 operation is guaranteed with the VIA FliteDeck suite of features that includes an integrated watchdog timer, remote LAN management and a host of monitoring tools.

The VIA EPIA EN Mini-ITX mainboard is fully compatible with all Mini-ITX, FlexATX and MicroATX chassis and associated accessories.

VIA EPIA EN Mainboard Specification		
<b>Model Name</b>	• VIA EPIA EN15000	• VIA EPIA EN12000E
<b>Processor</b>	• 1.5GHz VIA C7 Processor	• 1.2GHz VIA Eden Processor

<b>Chipset</b>	<ul style="list-style-type: none"> <li>• VIA CN700 North Bridge</li> <li>• VIA VT8237R-series South Bridge</li> </ul>
<b>System Memory</b>	<ul style="list-style-type: none"> <li>• 1 DDRII 400/533 DIMM socket</li> <li>• Up to 1GB memory size</li> </ul>
<b>VGA</b>	<ul style="list-style-type: none"> <li>• Integrated VIA UniChrome™ Pro AGP graphics with MPEG-2 accelerator</li> </ul>
<b>Expansion Slots</b>	<ul style="list-style-type: none"> <li>• 1 PCI</li> </ul>
<b>Onboard IDE</b>	<ul style="list-style-type: none"> <li>• 2 UltraDMA 133/100/66 Connectors</li> </ul>
<b>Onboard LAN</b>	<ul style="list-style-type: none"> <li>• VIA VT6122 GLAN Controller</li> </ul>
<b>Onboard Audio</b>	<ul style="list-style-type: none"> <li>• VIA VT1618 6 channel AC'97 Codec</li> </ul>
<b>Onboard TV Out</b>	<ul style="list-style-type: none"> <li>• VIA VT1625 HDTV Encoder</li> </ul>
<b>Onboard 1394</b>	<ul style="list-style-type: none"> <li>• VIA VT6307S IEEE 1394 Firewire</li> </ul>
<b>Back Panel I/O</b>	<ul style="list-style-type: none"> <li>• 1 PS2 mouse port</li> <li>• 1 PS2 keyboard port</li> <li>• 1 RJ-45 LAN port</li> <li>• 1 Serial port</li> <li>• 4 USB 2.0 ports</li> <li>• 1 VGA port</li> <li>• 1 RCA port (S/PDIF or TV out)</li> <li>• 1 S-Video port</li> <li>• 3 Audio jacks: line-out, line-in and mic-in (Horizontal, Smart 5.1 Support)</li> </ul>
<b>Onboard I/O Connectors</b>	<ul style="list-style-type: none"> <li>• 1 USB connector for 2 additional USB 2.0 ports</li> <li>• 1 1394 connector for 1 1394 port</li> <li>• 2 SATA Connector</li> <li>• 1 LPC connector</li> <li>• Front-panel audio connector (Mic and Line Out)</li> <li>• 1 Serial port connector for a second com port</li> <li>• 1 CIR connector (Switchable for KB/MS)</li> <li>• 2 Fan connectors: CPU/Sys FAN</li> <li>• 1 SMBUS connector</li> <li>• 1 S/PDIF in/out connector</li> <li>• 1 LVDS/TTL/DVI module connector (an add-on card is required)</li> <li>• ATX Power Connector</li> <li>• 1 Component (YPbPr) video pin header</li> </ul>
<b>BIOS</b>	<ul style="list-style-type: none"> <li>• Award BIOS, LPC 4/8Mbit flash memory</li> </ul>
<b>Operating System</b>	<ul style="list-style-type: none"> <li>• Windows 2000/XP, Linux, Win CE, XPe</li> </ul>
<b>Software Application</b>	<ul style="list-style-type: none"> <li>• VIA FliteDeck™ Utility</li> <li>• MissionControl-H/W Monitoring, Remote SNMP Management</li> <li>• FlashPort-Live BIOS Flash</li> <li>• SysProbe-Live DMI Browser</li> </ul>
<b>System Monitoring &amp; Management</b>	<ul style="list-style-type: none"> <li>• CPU temperature reading, CPU voltage monitoring</li> <li>• Wake-on-LAN, Keyboard-Power-on, Timer-Power-on, Watch Dog Timer, FAN control</li> <li>• System power management, AC power failure recovery</li> </ul>

---

<b>Operating Temperature</b>	<ul style="list-style-type: none"><li>• 0~50°C</li></ul>
<b>Operating Humidity</b>	<ul style="list-style-type: none"><li>• 0% ~ 95% (relative humidity; non-condensing)</li></ul>
<b>Form Factor</b>	<ul style="list-style-type: none"><li>• Mini-ITX (6 layer)</li><li>• 17 cm x 17 cm</li></ul>