



389.00 EUR  
incl. 19% VAT, plus shipping

- 12VDC based !
- 4x LAN ports

CARTFT.COM

Support: [Assembling Tutorial \[DE\]](#) | [Assembling Tutorial \[EN\]](#)

### Specifications

<a href="#">CPU</a>	Intel Pentium-M/Celeron-M @ 400 FSB	<a href="#">RAM</a>	2x DDR 266/333/400 low-profile
<a href="#">Graphic</a>	Intel Extreme Graphics	<a href="#">Audio</a>	AC97 Codec
<a href="#">Formfactor</a>	Barebone	<a href="#">Base</a>	Intel

### Interface

<a href="#">USB</a>	2x USB 2.0	<a href="#">LAN</a>	4x 10/100
<a href="#">Firewire</a>	1x	<a href="#">Parallel</a>	1x
<a href="#">IDE/SATA</a>	1x IDE	<a href="#">Serial</a>	1x

### Features

<a href="#">TV-Out</a>		<a href="#">Passive cooling</a>	
<a href="#">PCI</a>		<a href="#">PCI-Express</a>	
<a href="#">Mini-PCI</a>		<a href="#">PCMCIA</a>	
<a href="#">IDE</a>	■	<a href="#">SATA</a>	
<a href="#">DVI</a>		<a href="#">CPU changeable</a>	■
<a href="#">800x480 Resolution</a>	■	<a href="#">Compact Flash</a>	

CarPC-barebone for use with Intel Pentium-M/Celeron-M CPU.

<b>Processor (supported)</b>	Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher
<b>Memory</b>	Supports DDR 400/333/266 DIMM RAM 0.8" low profile 2x memory slots ! Maximum : 2 GB
<b>Video</b>	Intel Extreme Graphics 2 Supports up to 64MB DVMT video memory
<b>Audio</b>	Software AC '97 Audio CODEC

<b>Peripheral Connection</b>	Front : 3 x RJ45 10/100Mb Fast Ethernet 1 x IEEE 1394 Firewire port 1 x USB 2.0 / 1.1 Port 1 x MIC Port 1 x Ear Phone output Jack Power-on button Reset button Power-on and HDD LED  Rear : 1 x RS232 COM port 1 x parallel printer port 1 x RJ45 10/100Mb Fast Ethernet 1 x Line-Out output Jack 2 x USB 2.0 / 1.1 Ports 1 x 15 pin VGA 1 x 12v DC Power Jack input
<b>Storage</b>	One 2.5 inch Hard Disk and 9.5mm high. (Support Ultra DMA 33/66/100).
<b>Weight &amp; Size</b>	System approximately 3kg (fully equipped). System Dimension: 155 x 255 x 55 mm
<b>Power req.</b>	12V, 5A
<b>Accessory</b>	
<b>Storage</b>	Supports all Standard Slim CD-ROM/DVD-ROM, CD-RW, DVD-RW Combo Supports all 2.5" standard IDE hard drive, ATA-100/66/33.
<b>Scope of supply</b>	110V/230V EU power supply Barebone CPU Kühlkörper

Graphics driver for 800x480 resolution : [Here](#)