



999.00 EUR
incl. 19% VAT, plus shipping

- Sony CXD2951GA-4
- Waterproof !

The CTFGPS-1 GPS receiver features the new chipset Sony CXD2951GA-4, is waterproof and has a magnetic and rugged case bottom. The integrated highly sensitive GPS Aerial gives you a maximum reception quality.

The connection cable can be enlarged up to 5 meters for optimal placement of the receiver. The integrated USB-to-Serial bridge eases usage. For installation you only need a small USB driver.

Receiver	Tracking up to 12 satellites L1, 1575.42 MHz, C/A code
Accuracy	Position: 2DRMS approximately 2m, WAAS support Velocity: 0.1 m/s without SA imposed Time: $\pm 1\mu\text{s}$
Acquisition Time	Cold Start: 45s (Average) Warm Start: 35s (Average) Hot Start: 2s (Minimum)
Sensitivity	Acquisition: -139dBm Tracking: -152dBm
Dynamics	Max Altitude: 18000m Max Velocity: 500m/s Max Acceleration: $\pm 4g$
Navigation Update Rate	Once per second
Serial Port	TTL, RS232
Baud Rate	4800 bps (Optional 9600,19300,38400 bps)
Output Message	NMEA0283 V2.2 GGA, GSV, GSA, RMC (optional VTG, GLL)
Datum	WGS 84
Power Supply	DC 5V $\pm 5\%$
Power Consumption	Typical 80mA @5V
LED Indicator	Power On/Off Navigation
Operating Temperature	-40° ~ +85° C
Storage Temperature	-40° ~ +100° C
Humidity	5%~95%
Antenna Type	Built-in patch antenna