



999.00 EUR
incl. 19% VAT, plus shipping

- Celeron-M CPU onboard !
- Passive cooling !

Specifications

CPU	Celeron-M 800Mhz	RAM	1x DDR 266/333
Graphic	Intel Extreme Graphics	Audio	AC-97/DD5.1
Formfactor	ITX (17x17cm)	Base	Intel ITX

Interface

USB	4x USB 2.0	LAN	3x 10/100
Firewire	--	Parallel	1x
IDE/SATA	2x IDE, 2x SATA	Serial	4x

Features

TV-Out		Passive cooling	■
PCI	■	PCI-Express	
Mini-PCI		PCMCIA	
IDE	■	SATA	■
DVI		CPU changeable	
800x480 Resolution	■	Compact Flash	

Compatible enclosures

	Casetronic Travla C137		Casetronic Travla C138
	M300 Enclosure (1x PCI)		M300-LCD Enclosure (1x PCI)
	M350 Mini-ITX enclosure		M4-BOX
	MHero-L-B enclosure (1x PCI, Slimline ODD)		MHero-L-R enclosure (1x PCI, Slimline ODD) *new*



[MHero-S-B enclosure *new*](#)



[MHero-S-R enclosure *new*](#)



[Morex Case Cubid CB2699 beige](#)



[Morex Case Cubid CB2699 black](#)



[Morex Case Cubid CB3677 black](#)



[Morex Case Cubid CB3688 black](#)



[VoomPC \(perfect for M1-ATX/M2-ATX\) \[Black Edition\]](#)



[VoomPC \(perfect for M1-ATX/M2-ATX\) \[Black Edition\] \(with TFT power connector\)](#)



[VoomPC-2 \(perfect for M1-/M2-ATX\) \[Black Edition\]](#)



[VoomPC-2 \(perfect for M1-/M2-ATX\) \[Black Edition\] \(with TFT power connector\)](#)

The Kontron 886LCD-M/mITX(BGA) mainboard with onboard 800Mhz CPU is placed before VIA ITX C7 1.5 Ghz when it comparing performance !

It is a low cost, high feature passive cooling embedded Mini-ITX motherboard.

- Intel® Mobile Celeron® 800MHz 0KB L2 Cache(mBGA479) on board
- Passive cooling (No fan)
- Front Side Bus 400 MHz
- Intel® 855GME + Intel® 6300ESB Embedded Chipsets
- Intel® Extreme Graphics 2 Controller
- AGP/DVO slot
- Flat Panel Display Support (on board LVDS)
- Dual independent Display Support (incl. 2x LCD by optional ADD-Card)
- Up to 1GB PC2700/DDR333 SDRAM (incl. ECC)
- 3x 10/100 Mbps Ethernet
- 4x USB 2.0, 4x RS232C
- 1x ATA100 and 2x SATA150 IDE Controller
- On board RAID 0/1 support with SATA harddisk
- Compact Flash socket
- AC-97/DD5.1 sound including on board stereo amplifier
- Size: 170 x 170 mm (6.7" x 6.7")

Description

886LCD-M/mITX(BGA) is low cost passive cooling Embedded Mini-ITX motherboard with many up to date industrial features. The board is a variation of 886LCD-M/mITX Pentium-M Mini-ITX board. The board is based on Intel® 855GME/6300ESB Pentium-M support embedded chipset and available for long-term. 886LCD-M/mITX(BGA) is ideal for embedded applications which require passive cooling and many advanced PC technology features.

Scope of supply :

- Kontron 886LCD-M/mITX Mainboard BGA 800Mhz
- Kontron CPU-heatsink/fan (Onboard !)
- SATA-Cable

Graphics driver for 800x480 resolution : [Here](#)