



59.95 EUR
incl. 19% VAT, plus shipping

Support: [Heatsink-Height](#)

Specifications

CPU	Celeron 1.2 Ghz	RAM	1x DDR-II 400/533/677
Graphic	SiS Mirage	Audio	AD1888 Codec
Formfactor	ITX (17x17cm)	Base	Intel ITX

Interface

USB	6x USB 2.0	LAN	1x 10/100
Firewire	--	Parallel	1x
IDE/SATA	1x IDE, 2x SATA	Serial	1x

Features

TV-Out		Passive cooling	■
PCI	■	PCI-Express	
Mini-PCI		PCMCIA	
IDE	■	SATA	■
DVI		CPU changeable	
800x480 Resolution		Compact Flash	

Compatible enclosures



[CFI A-7879 Gehäuse \(4x 3.5" NAS, 1x 2.5", Hot-Plug, 1x PCI, 200W \) *new*](#)



[Casetronic Travla C137](#)



[Casetronic Travla C138 \(not in stock until 15.02.2012\)](#)





















[M200 Enclosure](#)



[M200-LCD Enclosure](#)



[M300 Enclosure \(1x PCI\)](#)

	M300-LCD Enclosure (1x PCI) [Delivery time on request]		M350 Mini-ITX enclosure
	M4-BOX		MHero-L-B enclosure (1x PCI, Slimline ODD)
	MHero-L-R enclosure (1x PCI, Slimline ODD) *new*		MHero-S-B enclosure *new*
	MHero-S-R enclosure *new*		Morex Case 3300
	Morex Case 3310		Morex Case 3777 black
	Morex Case Cubid CB2699 beige		Morex Case Cubid CB2699 black
	Morex Case Cubid CB3677 black		Morex Case Cubid CB3688 black
	VoomPC (perfect for M1-ATX/M2-ATX) [Black Edition]		VoomPC (perfect for M1-ATX/M2-ATX) [Black Edition] (with TFT power connector)
	VoomPC-2 (perfect for M1-/M2-ATX) [Black Edition]		VoomPC-2 (perfect for M1-/M2-ATX) [Black Edition] (with TFT power connector)

Minimum order quantity : 10 units !

The Intel® Desktop Board D201GLY2 is an innovative solution for the sub-value market segment. With an Intel® Celeron® processor and graphics integrated on the board, this board enables easy system integration and helps you to achieve a lower system cost. This board has 10/100 LAN, support up to six Hi-Speed USB 2.0 ports and 2 SATA (1.5 GB/s), providing both connectivity and ease of use for your computing needs such as email and Internet access, instant messaging and Voice Over IP (VoIP).

The Intel Desktop Board D201GLY2 is built in smaller uATX-Compatible form factor providing lower power consumption and passive thermal solution.

Form Factor	uATX (6.75 inches by 6.75 inches [171.45 millimeters by 171.45 millimeters]) (ITX compatible)
Processor	Integrated Intel® Celeron® 220 processor (1.2 GHz) with a 533 MHz system bus
Memory	One 240-pin DDR2 SDRAM Dual Inline Memory Module (DIMM) sockets Support for DDR2 677/533/400 MHz DIMMs Support for up to 1 GB of system memory
Chipset	SiS* SiS662 Northbridge SiS* SiS964L Southbridge
Audio	ADI* AD1888 audio codec
Video	Integrated SiS Mirage* 1 graphic engine

I/O Control	Winbond* W83627DHG-B based Legacy I/O controller for hardware management, serial, parallel, and PS/2* ports
LAN Support	10/100 Mbits/sec LAN subsystem using the Broadcom* LAN adapter device
Peripheral Interfaces	Six USB 2.0 ports One parallel ATA IDE interface with UDMA 33, ATA-66/100/133 support Two SATA ports One serial port One parallel port PS/2* keyboard and mouse ports
Expansion Capabilities	One PCI Conventional* bus connector

Note : The CPU heatsink has a height of 45mm. That's why it does not fit into every enclosure.

Compatible with :

- Voom
- Voom-2
- M300(-LCD)
- Travla C137

Not compatible with :

- M200(-LCD)
- Morex enclosures (without PCI slot)

PicoPSU & M3-ATX : You can only directly stick in the standard picoPSU-120 power supply. Other picoPSU models and M3-ATX can only be connected with an additional ATX extension cable.

For Operating you need a P4 adapter or a PSU with P4 connector