



999.00 EUR
incl. 19% VAT, plus shipping

- Intel Rapid BIOS Boot
- DDR-II RAM
- 1.2Ghz CPU
- SATA !

Specifications

CPU	Intel Celeron 220 1.2Ghz	RAM	1x DDR-II 400/533/677
Graphic	SiS Mirage	Audio	ADI* AD1888 audio codec
Formfactor	ITX (17x17cm)	Base	Intel ITX

Interface

USB	6x USB 2.0	LAN	1x 10/100
Firewire	--	Parallel	1x
IDE/SATA	1x IDE, 2x SATA	Serial	1x

Features

TV-Out		Passive cooling	
PCI	■	PCI-Express	
Mini-PCI		PCMCIA	
IDE	■	SATA	■
DVI		CPU changeable	
800x480 Resolution		Compact Flash	

Compatible enclosures



[Casetronic Travla C137](#)



[Casetronic Travla C138](#)



[M200 Enclosure](#)



[M200-LCD Enclosure](#)



[M300 Enclosure \(1x PCI\)](#)

















[M300-LCD Enclosure \(1x PCI\)](#)



[M350 Mini-ITX enclosure](#)



[M4-BOX](#)

	<u>MHero-L-B enclosure (1x PCI, Slimline ODD)</u>		<u>MHero-L-R enclosure (1x PCI, Slimline ODD) *new*</u>
	<u>MHero-S-B enclosure *new*</u>		<u>MHero-S-R enclosure *new*</u>
	<u>Morex Case 3300</u>		<u>Morex Case 3310</u>
	<u>Morex Case Cubid CB2699 beige</u>		<u>Morex Case Cubid CB2699 black</u>
	<u>Morex Case Cubid CB3677 black</u>		<u>Morex Case Cubid CB3688 black</u>
	<u>VoomPC (perfect for M1-ATX/M2-ATX) [Black Edition]</u>		<u>VoomPC (perfect for M1-ATX/M2-ATX) [Black Edition] (with TFT power connector)</u>
	<u>VoomPC-2 (perfect for M1-/M2-ATX) [Black Edition]</u>		<u>VoomPC-2 (perfect for M1-/M2-ATX) [Black Edition] (with TFT power connector)</u>

Note : Mainboard is like Intel D201GLY, but with fan !

The Intel® Desktop Board D201GLY2A is an innovative solution for the sub-value market segment. With an Intel® Celeron® processor and graphics integrated on the board, this board enables easy system integration and helps you to achieve a lower system cost. This board has 10/100 LAN, support up to six Hi-Speed USB 2.0 ports and 2 SATA (1.5 GB/s), providing both connectivity and ease of use for your computing needs such as email and Internet access, instant messaging and Voice Over IP (VoIP).

The Intel Desktop Board D201GLY2A is built in smaller uATX-Compatible form factor providing lower power consumption and passive thermal solution.

Form Factor	uATX (6.75 inches by 6.75 inches [171.45 millimeters by 171.45 millimeters]) (ITX compatible)
Processor	Integrated Intel® Celeron® 220 processor (1.2 Ghz) with a 533 MHz system bus
Memory	One 240-pin DDR2 SDRAM Dual Inline Memory Module (DIMM) sockets Support for DDR2 677/533/400 MHz DIMMs Support for up to 1 GB of system memory
Chipset	SiS* SiS662 Northbridge SiS* SiS964L Southbridge
Audio	ADI* AD1888 audio codec
Video	Integrated SiS Mirage* 1 graphic engine
I/O Control	Winbond* W83627DHG-B based Legacy I/O controller for hardware management, serial, parallel, and PS/2* ports
LAN Support	10/100 Mb/s/sec LAN subsystem using the Broadcom* LAN adapter device

Peripheral Interfaces	Six USB 2.0 ports One parallel ATA IDE interface with UDMA 33, ATA-66/100/133 support Two SATA ports One serial port One parallel port PS/2* keyboard and mouse ports
Expansion Capabilities	One PCI Conventional* bus connector

Note : The CPU heatsink has a height of 45mm. Thats why it does not fit into every enclosure.

Compatible with :

- Voom
- Voom-2
- M300(-LCD)
- Travla C137

Not compatible with :

- M200(-LCD) (needs [replacement heatsink](#))
- Morex enclosures (needs [replacement heatsink](#))

PicoPSU & M3-ATX : You can only directly stick in the standard picoPSU-120 power supply. Other picoPSU models and M3-ATX can only be connected with an additional ATX extension cable.

For Operating you need a P4 adapter or a PSU with P4 connector