



199.00 EUR  
incl. 19% VAT, plus shipping

- Mini-PCI Express
- 2x SO-DDR2
- Dual LAN
- ATI Direct X9 !

Support:  [Data Sheet](#) |  [Manual](#)

### Specifications

<a href="#">CPU</a>	AMD S1	<a href="#">RAM</a>	2x SO-DDR-II
<a href="#">Graphic</a>	ATI Radeon X1250	<a href="#">Audio</a>	Realtek ALC262
<a href="#">Formfactor</a>	ITX (17x17cm)	<a href="#">Base</a>	

### Interface

<a href="#">USB</a>	8x USB2.0	<a href="#">LAN</a>	2x 10/100/1000
<a href="#">Firewire</a>	2x	<a href="#">Parallel</a>	--
<a href="#">IDE/SATA</a>	1x IDE, 4x SATA	<a href="#">Serial</a>	--

### Features

<a href="#">TV-Out</a>		<a href="#">Passive cooling</a>	
<a href="#">PCI</a>	■	<a href="#">PCI-Express</a>	■
<a href="#">Mini-PCI</a>	■	<a href="#">PCMCIA</a>	■
<a href="#">IDE</a>	■	<a href="#">SATA</a>	■
<a href="#">DVI</a>	■	<a href="#">CPU changeable</a>	■
<a href="#">800x480 Resolution</a>		<a href="#">Compact Flash</a>	

### Compatible enclosures



[CFI A-7879 enclosure \(4x 3.5" NAS, 1x 2.5", Hot-Plug, 1x PCI, 200W \) \\*new\\*](#)



[Casetronic Travla C137](#)



[Casetronic Travla C138](#)












[M300 Enclosure \(1x PCI\)](#)



[M300-LCD Enclosure \(1x PCI\)](#)



[M350 Mini-ITX enclosure](#)

	<a href="#"><u>M4-BOX</u></a>		<a href="#"><u>MHero-L-B enclosure (1x PCI, Slimline ODD)</u></a>
	<a href="#"><u>MHero-L-R enclosure (1x PCI, Slimline ODD) *new*</u></a>		<a href="#"><u>MHero-S-B enclosure *new*</u></a>
	<a href="#"><u>MHero-S-R enclosure *new*</u></a>		<a href="#"><u>Morex Case Cubid CB2699 beige</u></a>
	<a href="#"><u>Morex Case Cubid CB2699 black</u></a>		<a href="#"><u>Morex Case Cubid CB3677 black</u></a>
	<a href="#"><u>Morex Case Cubid CB3688 black</u></a>		<a href="#"><u>VoomPC (perfect for M1-ATX/M2-ATX) [Black Edition]</u></a>
	<a href="#"><u>VoomPC (perfect for M1-ATX/M2-ATX) [Black Edition] (with TFT power connector)</u></a>		<a href="#"><u>VoomPC-2 (perfect for M1-/M2-ATX) [Black Edition]</u></a>
	<a href="#"><u>VoomPC-2 (perfect for M1-/M2-ATX) [Black Edition] (with TFT power connector)</u></a>		

D2703-S is a special designed mainboard for industrial applications. Extended temperature ranges, long life capacitors and a special tin-plated PCB built an optimal hardware basis for industrial systems. Additionally we offer an extended availability (up to 48 months) and additional hardware and software documentation. D2703-S provides dual GBE LAN Ethernet, Controller on board, Serial ATA II RAID, Audio on board (HDA), ATI Radeon Graphics, CF support for Embedded OS, USB 2.0, Instantly Available PC (IA-PC) and Improved Thermal Management/System Monitoring.

Board Size	Mini-ITX: 6.7" x 6.7" (170 x 170 mm)
Chipset	AMD M690E & SB600
Memory	2 SO DIMM Sockets (1.8V), 256MB - 8GB, Single Channel or Dual Channel DDR2 800/667 SDRAM, unbuffered, no ECC
Processors	AMD Mobile Turion™ 64 X2 Dual Core Processors AMD Mobile Sempron™ Processors Mobile Socket S1g1 (PGA 638), max. 35W, HyperTransport™ 1; 800MHz BTX12V (24 Pin) or ATX12V (20 Pin) Power Supply required Support for Soft-Off Power Supplies or 24V / 5A via DC-connector (Rear I/O connector or onboard connector)
Power Specification	5V and 3.3V Supply Voltage on PCI Slots (PCI Rev. 2.3) 3.3V Auxiliary Supply Voltage on PCI Slots (Wake-Up Function) On board CPU Voltage Regulator, 5V / 2A Auxiliary Power (BTX/ATX only) required for USB Wake-Up from Save-to-RAM, Save-to-Disk Integrated ATI Radeon X1250 graphics; shared memory (up to 256MB); DirectX 9 compliant; DVI, VGA and Dual Channel LVDS support Realtek ALC262 (HD Audio); HW 3D Stereo Enhancement; SW Wavetable Synthesis Support Dual Realtek RTL8111C 10/100/1000 Ethernet controller
Graphics	
Audio	
LAN	

---

Drives	1x ATA 133 Interface for 1 Drive 4x Serial ATA II 300 Interfaces (max 3 GBit/s); up to 4 Drives; RAID 0/1/10 1x CF Interface (Typ I)
BIOS	Phoenix TrustedCore BIOS Version V6.00 modified and adapted by Fujitsu Siemens Computers; Recovery BIOS, SM-BIOS (DMI), BIOS Update via USB (stable user settings), Quick Boot, Logo Boot, Quiet Boot, Plug & Play, Automatic DRAM and PCI Configuration, BIOS Support for S.M.A.R.T., Advanced Power Management, ACPI S3 (Save-to-RAM), ACPI S4 (Save-to-Disk), Wake on time from S5; Flexible LVDS Support Silent Fan : Independent temperature related processor fan and system fan supervision and control
Special Features	System Guard : View and adjust Silent Fan Silent Drives Noise reduction for optical and hard disk drives Recovery BIOS : Restores a corrupted BIOS Desk Update Simple driver update with Driver&Utilities DVD Multi Boot : Comfortable boot from any boot device

**Scope of supply :**

- Fujitsu D2703-S Mainboard
- Fujitsu CPU-heatsink/fan
- 1x SATA cable
- 1x IDE cable

