



164.00 EUR
incl. 19% VAT, plus shipping

- HDMI !
- HDTV !

Specifications

CPU	VIA C7 1.5Ghz	RAM	1x DDR-II 400/533
Graphic	VIA Unichrome Pro II	Audio	VIA VT1708A 6-Kanal HD Audio CODEC
Formfactor	ITX (17x17cm)	Base	VIA ITX

Interface

USB	6x USB 2.0	LAN	1x 10/100
Firewire	1x	Parallel	--
IDE/SATA	2x IDE, 2x SATA	Serial	2x

Features

TV-Out	■	Passive cooling	
PCI	■	PCI-Express	
Mini-PCI		PCMCIA	
IDE	■	SATA	■
DVI		CPU changeable	
800x480 Resolution		Compact Flash	

Compatible enclosures



[Casetronic Travla C137](#)



[Casetronic Travla C138](#)



[M200 Enclosure](#)



[M200-LCD Enclosure](#)



[M300 Enclosure \(1x PCI\)](#)



[M300-LCD Enclosure \(1x PCI\)](#)



[M350 Mini-ITX enclosure](#)



[M4-BOX](#)



[MHero-L-B enclosure \(1x PCI, Slimline ODD\)](#)



[MHero-L-R enclosure \(1x PCI, Slimline ODD\) *new*](#)



[MHero-S-B enclosure *new*](#)



[MHero-S-R enclosure *new*](#)



[Morex Case 3300](#)



[Morex Case 3310](#)



[Morex Case Cubid CB2699 beige](#)



[Morex Case Cubid CB2699 black](#)



[Morex Case Cubid CB3677 black](#)



[Morex Case Cubid CB3688 black](#)



[VoomPC \(perfect for M1-ATX/M2-ATX\) \[Black Edition\]](#)



[VoomPC \(perfect for M1-ATX/M2-ATX\) \[Black Edition\] \(with TFT power connector\)](#)



[VoomPC-2 \(perfect for M1-/M2-ATX\) \[Black Edition\]](#)



[VoomPC-2 \(perfect for M1-/M2-ATX\) \[Black Edition\] \(with TFT power connector\)](#)

- VIA CX700M Single chipset Technology
- Support Front Side Bus 533MHz
- Support 2 Serial ATA 2 Devices with RAID 0, 1
- Support PCI 120-Pin Adapter Conn. With Expansion Daughter-boards
- Gigabit Ethernet LAN Supported
- 6 Channel HD Audio CODEC
- VIA VT6307 IEEE1394a Controller
- VIA VT1622A TV Encoder
- 17 x 17CM Mini-ITX Form Factor

Form Factor	Mini-ITX Express Motherboard
CPU	VIA C7 1.5GHZ CPU (12W)
Memory	1 * 240-pin DIMM Sockets for DDR2 533 up to 1 GB
Chipset	VIA CX700M Single Chipset
Power Management	ACPI S3 Compliant ,supports power saving mode
PCI enhanced IDE	2* Ultra DMA 133 / 100 / 66 IDE Devices Support
Serial ATA Interface	2 Serial ATA2 HDDs with RAID 0, 1 Function Support
VGA Interface	VIA Unichrome Pro II
Video Memory	Share Memory up to 128MB
Audio Interface	VIA VT1708A 6-Channel HD Audio CODEC
LAN Interface	VIA VT6122 10 / 100 / 1000 PCI LAN
Extended Interface	1 * 32-bit PCI Slot 1 * PCI 120-Pin Adapter Connector with Expansion Daughter Boards

Internal I/O Port	<ul style="list-style-type: none"> 2 * High Speed USB Connectors for 4 USB 2.0 Ports 1 * CPU Smart Fan Connector, 2 * Chassis Fan Connectors 2 * 9-Pin COM Port Connector 1 * CD / AUX Audio in & SPEAK Out 1 * HDTV Out Connector 1 * IrDA (SIR) 1 * 6-pin Video Input Pin-header 1 * PCI 120-Pin Adapter Conn.
External I/O Port	<ul style="list-style-type: none"> 2 * High Speed USB Connectors @ 480 M-bit / s 1 * D-Sub 15-pin VGA Connector 1 * HDMI Port 1 * PS / 2 Mouse & 1 * PS/2 Keyboard 1 * RJ45 Connector 1 * Audio I / O 1 * IEEE 1394a Connector
BIOS	Award 4 MB Flash ROM
Power Requirement	Standard 24-Pin ATX Power supply
Dimension	170mm x 170mm