




549.00 EUR incl. 19% VAT, plus shipping

- -20 °C to 70 °C
- 4x COM
- 8-25V DC input!
- 2x PCI, 1x PCI-E!



Support: Specifications [EN]

It is an Intel® Atom<sup>TM</sup> D525 IPC. It is, moreover, a reliable embedded fanless IPC. Nuvo-2000 accommodates up to three PCI/PCIe cards and two 2.5" hard drives in its shoe-box size. More than that, it provides versatile I/O interfaces such as COM ports, USB ports, Gigabit Ethernet port, parallel port and mini-PCIe port, not to mention that the isolated DIO channels can be integrated optionally into this compact box.

Leveraging Intel® Atom™ D525 1.8GHz dual-core processor, Nuvo-2000 delivers adequate computing performance for most Industrial applications. We also give Nuvo-2000 ingenious design mechanically and electronically so it can have a reliable, embedded fanless operation in the temperature range of -20 to 70°C.

Nuvo-2000 is designed for general-purpose usage. Its compact size, PCI/PCIe slots and simple yet useful I/O functions fit most applications where wall-mount IPC is currently deployed. And, what is more, the embedded fanless design of Nuvo-2000 gives you much more reliability than an ordinary IPC in all kinds of environments.

System Core

Processor

Intel® Atom™ D525 1.8GHz dual-core processor

Chipset

Intel® ICH8-M I/O Control Hub

## Nuvo-2021 (Intel Atom D525, 2xPCI, 1xPCI-E) [FANLESS]

[http://www.cartft.com/catalog/il/1475]



Graphics	Integrated Intel® GMA 3150 graphics
Ciapinos	integrated intel® OWA 5 100 graphics

Memory 1x 204-pin SO-DIMM socket, up to 4GB DDR3 800MHz SDRAM

Front-panel I/O Interface

Ethernet 1x Intel® 82574L Gigabit Ethernet port

Video Port 1x DB-15 connector for analog RGB, supporting 2048x1563

resolution

Serial Port 1x software-programmable RS-232/422/485 (COM1)

1x RS-232 (COM2)

USB 4x USB 2.0 ports

KB/MS 1x 6-pin Mini-Din for PS/2 keyboard and mouse

Audio 1x Mic-in and 1x Speaker-out

Internal I/O Interface

Serial Port 2x RS-232 (COM3 & COM4)

Parallel Port 1x Parallel port

Mini-PCIe 1x mini PCI Express slot with SIM socket

Isolated DIO 12-CH isolated DI + 12-CH isolated DO (Optional)

Storage Interface

SATA HDD 2x Internal SATA ports for 2.5" HDD/SSD installation

CompactFlash 1x Type I & II CF socket

**Expansion Bus** 

PCI 3x PCI slots (Nuvo-2030)
2x PCI slots (Nuvo-2021)

1x PCI slot (Nuvo-2010)

PCI Express 1x PCI Express x4 slot (Nuvo-2021 only)

**Power Supply** 

DC Input Built-in 8~25 VDC DC input

Input Connector 1x 2-pin pluggable terminal block for DC input

1x DC jack (ø2.5) for AC/DC adapter input

Mechanical

Dimension 141 mm (W) x 157mm (H) x 226 mm (D)

Weight 2.9 kg (including one 2.5" HDD and DDR3 SODIMM)

Mounting Wall-mount by mounting bracket

Environmental

Operating Temperature

Standard model: -20°C~70°C, 100% CPU loading \*/\*\*

Extended temperature model: -20°C~70°C, 100% CPU loading \*/\*\*

StorageTemperature -40°C ~ 85°C

Humidity 10%~90%, non-condensing

Vibration Operating, 5 Grms, 5-500 Hz, 3 Axes

(w/ SSD, w/o add-on card, according to IEC60068-2-64)

Shook Operating, 50 Grms, Half-sine 11 ms Duration

(w/ SSD, w/o add-on card, according to IEC60068-2-27)

EMC CE/FCC Class A, according to EN 55022 & EN 55024

