



159.00 EUR  
incl. 19% VAT, plus [shipping](#)



Support:  [Specifications \[EN\]](#)

- Intel Atom D525 + NM10 Chipset
- Support INTEL® Atom Dual-Core D525 CPU
- Support 2 \* 3Gb/s SATA■
- Support 2 \* DDR3 800MHz Single CH SO-DIMM up to 4GB
- Supports 2 \* Gigabit LAN
- Support 6 \* COM ports (COM2 for RS232/422/485)
- Integrated Realtek ALC662 HD Audio CODEC with 6-CH
- Support Watchdog Technology
- Support CPU Smart FAN
- Mini-ITX Form Factor(170mm x 170mm)
- **CPU**
  - INTEL ® Atom Dual-Core Processor D525 (45nm,1.80GHz,1024MB L2 Cache)
- **Chipset**
  - INTEL® Atom D525 + NM10
- **Memory**
  - 2 \* DDR3 800MHz Single CH SO-DIMM up to 4GB
- **Expansion Slots**
  - 1 \* PCI slot, 1 \* Mini PCI-E socket
- **Storage**
  - 2 \* Serial ATA2 3Gb/s connectors
- **Audio**
  - Realtek ALC662 6-Channel HD Audio CODEC
- **Ethernet LAN**
  - 2 \* Realtek RTL8111EVL Gigabit LAN
- **LVDS**
  - Onboard 18-bit single channel LVDS connector

- **USB**
  - Embedded 7 \* USB 2.0/1.1
  -
- **Rear Panel I/O**
  - 4 \* USB 2.0/1.1 ports
  - 1 \* PS/2 Mouse & Keyboard connector
  - 2 \* RJ-45 port
  - 3 \* Audio I/O ports ( Line-in, Mic and Line-out )
  - 1 \* VGA port
  - 1 \* COM port
  - 1 \* Parallel port
- **Internal I/O**
  - 3 USB 2.0 ports
  - 3 \* NB / Chassis Fan connectors;
  - 1 \* 24-pin ATX Power connector
  - 1 \* LVDS header/ 1\* CD IN /1 \* GPIO
  - 1 \* AUDIO header
  - 5 \* COM headers (COM2 for RS232/RS422/RS485)
- **BIOS**
  - AMI 8MB DIP Flash ROM
- **Functional**
  - ATM, Automation, Medical Equipment, Networking, POS Machine, General Application, Transportation
- **Packing**
  - Color Box Dimension ■200(W) x 200(D) x 70(H)mm
- **Certificate**
  - CE, FCC, RoHS
- **Temperature**
  - Operating within 0~40 centigrade
  - Storage within -20-85 centigrade
- **Form Factor**
  - Mini ITX Form Factor(17cmx17cm)

**Product Accessories**

- 3x COM cable
- Manual
- CD
- 1x SATA cable
- I/O shield