

389.00 EUR
incl. 19% VAT, plus shipping

- INTEL® Celeron 1037U Processor + NM70 Chipset
- Support 1 * DDR3 1600/1333MHz Single CH up to 8GB
- Support 1 * Serial ATAII (3Gb/s) & 1 * Serial ATAIII (6Gb/s) Devices
- Integrated Realtek ALC662 HD Audio CODEC with 2-CH
- 1 * 24 bits Dual Channel LVDS header
- Supports 2 * Realtek RT8111F Gigabit LAN
- Support 6 * COM ports (COM1 support RS232/422/485)
- 6 * COM support +5V/+12V
- Support Watch dog Technology
- Provides AT mode power
- Support CPU Smart FAN
- Compliance with ErP standard
- Mini-ITX Form Factor (170mm x 170mm)

• **CPU**	• INTEL® Celeron 1037U Dual Core Processor (1.8GHz)
• **Chipset**	• INTEL®NM70 Express chipset
• **Memory**	• 1 * DDR3 1600/1333MHz Single CH SO-DIMM up to 8GB
• **Expansion Slots**	• 1 * PCI –E x 1 slot • 1 * half size Mini PCI-E socket
• **Storage**	• 1 * Serial ATA2 3Gb/s & 1 * Aerial ATA3 6Gb/s connectors • 1 * full size mSATA socket

Audio	Realtek ALC662 6-Channel HD Audio
Ethernet LAN	2 * RTL8111F PCI-E Gigabit LAN
LVDS	Onboard 1 * 24-bits Dual channel connector
USB	Embedded 6 * USB 2.0/1.1
Special Features	Support ACPI S3 Support CPU Smart FAN Support Watch Dog
Rear Panel I/O	4 * USB 2.0/1.1 ports 2 * RJ-45 ports 2 * Audio I/O ports (MIC and Line-out) 1 * VGA port 1 * Parallel port 1 * HDMI port 1 * COM port (COM1 for RS232/422/485) 1 * PS/2 1 * RJ-11 port 1 * 12V DC in jack
Internal I/O	1 * USB 2.0/1.1 headers for 2 USB 2.0 ports 2 * NB / Chassis Fan connectors 5 * COM headers 1 * LVDS headers /1 * Inverter headers 1 * AUDIO header 1 * Chassis Intrusion
BIOS	AMI 32MB UEFI DIP Flash ROM
Functional	POS Machine
Packing	Color Box Dimension■200(W) x 200(D) x 70(H)mm
Certificate	CE, FCC, RoHS
Temperature	Operating within 0~40 centigrade Storage within -20-85 centigrade
Form Factor	Mini ITX Form Factor(17cmx17cm)