Jetway NF9KC-1047 (Intel HM65)
[http://www.cartft.com/catalog/il/1767]

249.00 EUR
incl. 19% VAT, plus shipping

- INTEL® Celeron 1047UE Processor + HM65 Chipset
- Support 2 * DDR3 1600/1333MHz Dual CH up to 16GB
- Support DirectX 9 Graphics
- Support 1 * Serial ATAII (3Gb/s) & 1 * Serial ATAIII (6Gb/s) Devices
- Integrated Realtek ALC662 HD Audio CODEC with 2-CH
- 2 * 24 bits Dual Channel LVDS header
- Supports 1 * Realtek RT8111F Gigabit LAN
- Support 4 * COM ports (COM1 & COM4 support RS232/422/485)
- Support Windows 8
- Support Watch dog Technology
- Support +9V~+24V Wide range power DC-in
- Support CPU Smart FAN
- Compliance with ErP standard
- Thin Mini-ITX Form Factor (170mm x 170mm)

• **CPU**	• INTEL® Celeron 1047UE Dual Core Processor (1.4GHz)
• **Chipset**	• INTEL®HM65 Express chipset
• **Memory**	• 2 * DDR3 1600/1333MHz Dual CH SO-DIMM up to 16GB

• **Expansion Slots**	• 1 * PCI –E x 16 slot
• **Storage**	• 1 * Serial ATA2 3Gb/s & 1 * Serial ATA3 6Gb/s connectors • 1 * full size mSATA socket (Selectable W/Mini PCI-E)
• **Audio**	• Realtek ALC662 2-Channel HD Audio
• **Ethernet LAN**	• 1 * RTL8111F PCI-E Gigabit LAN
• **LVDS**	• Onboard 2 * 24-bits Dual channel connector
• **USB**	• Embedded 7 * USB 2.0/1.1 •
• **Special Features**	• Support ACPI S3 • Support CPU Smart FAN • Support Watch Dog
• **Rear Panel I/O**	• 3 * USB 2.0/1.1 ports • 1 * RJ-45 port • 1 * Line-out connector • 1 * HDMI port • 1 * COM port (COM1 for RS232/422/485) • 1 * +9V~+24V DC in jack
• **Internal I/O**	• 2 * USB 2.0/1.1 headers for 4 USB 2.0 ports • 1 * VGA header • 1 * PS/2 header • 1 * Chassis Intrusion • 2 * NB / Chassis Fan connectors; • 2 * LVDS headers /2 * Inverter headers • 1 * AUDIO header • 1 * Chassis Intrusion
• **BIOS**	• AMI 32MB UEFI DIP Flash ROM
• **Functional**	• Panel PC, All-in-One PC, Digital Signage, POS Machine
• **Packing**	• Color Box Dimension：200(W) x 200(D) x 70(H)mm
• **Certificate**	• CE, FCC, RoHS
• **Temperature**	• Operating within 0~40 centigrade • Storage within -20-85 centigrade
• **Form Factor**	• Thin Mini ITX Form Factor(17cmx17cm)