

164.00 EUR  
incl. 19% VAT, plus [shipping](#)



- Intel® Celeron™ J1900 (2.0 GHz) quad-core processor
- Support DirectX 11 3D Graphics Acceleration
- Support DDR3L 1333
- Integrated HD Audio CODEC
- Support PCI Express Gigabit LAN
- Support 1\*USB3.0 Port
- Support 24-bit Dual channel LVDS
- Onboard 1\*MiniPCI-E connector
- Onboard 1 \*M- SATA connector
- 2 Phase CPU Power Support
- Support Thunder Protection Function
- [Thin mini ITX](#) Form Factor(170mm X170mm)

<b>CPU-Chipset</b>	<ul style="list-style-type: none"> <li>• INTEL® Celeron™ J1900 (2.0 GHz) quad-core processor</li> <li>• 2 Phase CPU Power Support</li> </ul>
<b>I.O Chipset</b>	<ul style="list-style-type: none"> <li>• Fintek F71808EC</li> </ul>
<b>Memory</b>	<ul style="list-style-type: none"> <li>• 2*SO-DIMM slot</li> <li>• Support DDR3L 1333</li> <li>• Max. capacity of system memory up to 16GB</li> </ul>

• <b>Expansion Slots</b>	• 1 * MiniPCI-E connector
• <b>Storage</b>	• 1* Serial ATA2 3Gb/s connector(CO-LAY M-SATA) • 1 * <a href="#">M-SATA Connector</a>
• <b>Audio</b>	• ALC887 Audio CODEC • HD Audio CODEC
• <b>Ethernet LAN</b>	• Realtek® RTL8111G Chip • PCI Express Gigabit LAN
• <b>LVDS</b>	• Onboard 24-bit Dual channel
• <b>USB</b>	• 1* USB3.0 (EXT) • 2* USB 2.0/1.1(2 distribute in back panel)
• <b>Special Features</b>	• Support CPU Smart Fan • Support Watch dog Technology • Support GPIO Technology • Support Amplifier function(3W) • Thunder Protection Function • All Solid Capacitor design for CPU
• <b>Back Panel I / O</b>	• 1* PS/2 port • 2* USB 2.0/1.1 ports • 1* USB 3.0 port • 1* RJ-45 port • 1* DVI port • 1* VGA port • 1* 3-JACK
• <b>Internal I / O</b>	• 2*CPU / Chassis Fan connectors • 1*COM header • 1 *24-pin ATX Power connector • 1 *24-bit Dual Channel LVDS header • 1 *GPIO header • 1 *Mini PCI-e connector • 1 * M-SATA Connector • 1* SATA Connector • 1 * Audio header • 1 * Front panel header
• <b>BIOS</b>	• AMI 64MB DIP Flash ROM
• <b>Form Factor</b>	• Thin mini ITX Form Factor(170mm X 170mm)