FleetPC-4-D Car-PC (Intel Celeron N3060 2x2.48Ghz, Autostart-Controller, 9-36V Automotive PSU, GPS) [FANLESS]

[http://www.cartft.com/catalog/il/2169]

849.00 EUR

incl. 19% VAT, plus shipping

- **Fanless ! GPS !**
- **Auto Power On/Off !**
- **eMark certified !**
- **VBOX-3130**

Support: Specifications | Manual [EN] | Drivers (Win7+8+10) | Test Tools | Drawing

This MiniPC was especially designed for fleet applications. The Car-PC can be connected directly to the car battery (12V/24V). Based on ignition plus, the PC will start and shutdown.

For a full PC you need in addition :
- 2.5" HDD/SSD or SATA DOM module - 1x SO-DDR-3L RAM (up to 8GB)

The PC is completely fanless and is equipped with an Intel Celeron N3060 2x2.48GHz CPU.

Available additional modules:
The PC comes with 4x antenna-output and 3x Mini-PCIe slots (1x occupied by GPS module).
We recommend these modules:
- HSPA / UMTS / EDGE Mini-PCIe Modem (Huawei MU609)
- Wireless LAN / Bluetooth Mini-PCI Express [Qcom Combo]

Features :
- Fanless
- Intel Dual Core Celeron N3060 2.48GHz CPU
- Integrated, intelligent Automotive power supply
- 3x RS232
- GPS (ublox 6 with G-sensor)
- 2x Gigabit LAN
- DVI-I + HDMI
- Watchdog
- Prepared for GPS, WLAN, GSM/GPRS with ext. antennas
- 2 x DI / 2 x DO with Relay 12V / 100mA

- Vibration/shock tested

For FleetPC-4-D we offer an direct connector cable for our TFT-dispays.

Dimensions / Weight	182mm W x 167.6mm D x 54mm H, 1.4kg
CPU	Intel Dual Core Celeron N3060 2.48 GHz
RAM	1x SO-DDR-3L RAM (up to 8GB)
Graphics	Intel HD Graphics
GPS	VDB-800SG (ublox 6 with G-sensor)
Expansion	- 3x Mini-PCIe
OS Support	Windows 7, Windows 8.1, Windows 10, Linux
Vibration & Shock	MIL-STD-810F
Operating temperature	-40~70°C (with SSD)
Certification	CE, FCC, eMark
I/O	- 2x Gigabit LAN (Intel i210-AT) - 3x RS232 (2 with 232/422/485) - 2x USB3.0 - 1x USB2.0 - GPIO port (2in, 2out, with Relay 12V/100mA) - Mic-In, SPK Out - 1x DVI-I (for DVI-D and VGA), 1x HDMI - 4x SMA Antenna hole (for eg. GPS, GSM/ GPRS/3G, WLAN, Bluetooth)
Drive bays	1 x 2.5" SATA HDD/SSD drive bay, 1x SATA DOM
Power supply	9~36V DC PSU included - Power off Delay Time Setting by Software, Default 5min - Backup Battery Kit (optional)
Scope of supply	- FleetPC-4-D PC with Intel Celeron N3060 (2x2.48Ghz), mounting brackets - 1x Pigtail + Antenna for GPS