



209.00 EUR
incl. 19% VAT, plus [shipping](#)

- Rockchip® ARM Cortex A17 RK3288 Quad-core 1.8GHz
- On board 1333/2GB DDR3L DRAM up to 4GB)
- On board 8G Flash ROM up to 64GB
- 1* Realtek GbE, 1* RS232, 2* UART, 1* Debug, 6* USB2.0, 1* OTG (Co-lay USB2.0)
- 1* HDMI, 1* eDP, 1* 24-bits Dual CH LVDS, 1* MIPI DSI, 1* MIPI CSI
- 1* Micro SD Max 64GB)
- Support 802.11 b/g/n 2.4G, BT-V4.0
- Support Android 5.1 and Debian9.0

Model	
Model	– JR3288LC-2N
Part Number	– JR3288LC-2N
Form Factor	
Dimensions	– 120 * 72mm
Processor System	
Processor/CPU	– Rock Chip® ARM Cortex A17 RK3288 Quad-core 1.8GHz – Rock Chip® RK808-B PMU
Memory	
DRAM	– Onboard DDR3L 1333MHz 2GB
Expansion Slot	
Dimensions	– 1* Micro SD
Graphics	
Graphics	– Mali T764 GPU,shared memory – 1* HDMI (Max Resolution: 1920x1080@60Hz) – 1* LVDS (Max Resolution: 1920x1200@60Hz) – 1* eDP (Max Resolution: 2560x1600@60Hz) – 1* MIPI DSI (Max Resolution: 1920x1080@60Hz) – Support Dual Displays
Ethernet	
Ethernet	– 1* Realtek RTL8211E-VB GbE

Wifi	- 1* Realtek RTL8723BS 802.11b/g/n 2.4G WIFI and BT-V4.0
Audio	
Audio	- 2 channel HD audio: ES8316
Storage	
Storage	- 8GB Flash ROM (Max 64GB)
I/O Port	
Rear I/O	- 1* DC Jack (12V) - 2* USB2.0 (USB1 Co-lay OTG) - 1* HDMI - 1* AUDIO - 1* Micro SD - 1* Ethernet
Internal I/O	- 4* USB2.0 - 3* UART (CON36/39: TTL■CON47: for Debug, CON36 Co-lay RS232/485) - 1* RS232 (CON37) - 1* LVDS / Inverter - 1* eDP - 1* MIPI DSI - 1* MIPI CSI - 1* Speaker (3W AMP) - 1* GPIO (4 bit) - 1* I2C
Watchdog Timer	
Watchdog Timer	- From Super I/O to drag RESETCON# - 256 segments (0 ~ 255 sec)
Power	
Power	12V DC-in (PWR Con) - AT : Directly PWR on as Power input ready - ATX: Press Button to PWR on after Power input ready
Compliance	
Certifications	- CE, FCC, LVD, RoHS, REACH
Environment	
Temperature	- Operating: -10°C ~ 60°C
	- Storage: -20°C ~ 70°C
Warranty	
Warranty	- 2 Years Limited Warranty