



79.95 EUR
incl. 19% VAT, plus [shipping](#)

- M.2 NGFF !
- UMTS / 3G !
- LTE (EUROPE) !

Support:  [Specifications](#) | [Drivers \(Windows\)](#) | [Dialer Software](#)

The ME906E is a LTE module with NGFF interface , supporting LTE (FDD) B1/B2/B3/B5/B7/B8/B20,Penta-band DC-HSPA+/HSPA+/HSPA/WCDMA for Europe network coverage, low power consumption, Global Navigation Satellite System(GNSS), and European carrier certifications, enabling easier and more flexible design and integration into end devices. In addition, the ME906E supports NGFF features to optimize performance, power consumption, and usability.

ME906E is the ideal choice for Ultrabook, notebook, tablet etc.

Manufacturer	Huawei
Model	ME906E
Unlocked	Ready for use with global services. No contract required.
Network Bands	<ul style="list-style-type: none"> • LTE (FDD) B1/B2/B3/B5/B7/B8/B20 Quad-band DC-HSPA+/HSPA+/HSPA/UMTS B1/B2/B4/B5/B8 Quad-band EDGE/GPRS/GSM 1900/1800/900/850 MHz GPRS/EDGE: Multi-slot Class 12
Data Speed	WCDMA PS: UL (384 kbps)/ DL (384 kbps) DC-HSPA+ :UL (5.76 Mbps)/ DL (42 Mbps) LTE FDD: UL (50 Mbps)/ DL (100 Mbps) @Bandwidth 20M (CAT3) Antenna interfaces x 2
Interface	M.2 Socket 2 USB 2.0 interface high speed Power supply UICC interface
Power Supply	Supply voltage range:3.135V~4.4V (3.3 V recommended) Normal operation: -10°C to +55°C
Temp Range	Extended operation: -20°C to +70°C Storage: -40°C to +85°C
GPS	GNSS: GPS Standalone, A-GPS, GPS XTRA, Glonass
Dimensions	<ul style="list-style-type: none"> • 42x30x2.3 mm

Supported Systems

Windows 7/Windows 8/Android 4.0 or above
SIM Hotswap
IPV6
BodySAR

Special Features

Ultrabook feature support(ACT, WiFi Offload , DPTF)
Tunable Antenna
Supporting MO and MT
Supporting formats of PDU
Point-to-point and cell broadcast

Package Contents

New Huawei ME906E NGFF Embedded Module.